

DEFINITION


series MP4

SERIES
Materials and finishes (meets RoHS requirements)
MP4 Cable: stainless steel Retainer bars: aluminium alloy Inserts: stainless steel

INTERFACES	
fixtures holes D	Bar 1
Bar 2	
1 through hole ø5,8 mm (option:Insert M8)	Bar 1


SERIE: MP4 **MODEL:** -90
'Polycal' mount from height: 40mm
the MP4 series width: 47mm
weight: 0,07kg






COMPRESSION AND TENSION

MP4 Series	Model	-90	-120	-145	-195
1.Max Static	F daN	2,8	2,4	1,6	1
	d mm	2,8	4,3	5,8	8,4
2.Max Shock	F daN	8,5	7,3	4,8	3,1
	d mm	15	24	31	45
3.Max Vibration	2a mm	1,7	2,7	3,5	5
	f Hz	11,6	9,5	8,2	6,9
1.Max Static	F daN	2,8	2,4	1,6	1
	d mm	2,5	2,9	4,2	5,8
2.Max Shock	F daN	33,1	21,9	15,4	9,6
	d mm	12	11	17	23
3.Max Vibration	2a mm	1,4	1,3	2	2,6
	f Hz	14,1	13,8	11,3	9,8



COMPRESSION/ROLL 45° - TENSION/ROLL 45°

MP4 Series	Model	-90	-120	-145	-195
1.Max Static	F daN	2,1	1,8	1,2	0,8
	d mm	3,9	4,9	7,4	11,3
2.Max Shock	F daN	5,7	4,7	3,1	2
	d mm	22	36	47	68
3.Max Vibration	2a mm	2,5	4	5,2	7,6
	f Hz	8,7	7,2	6,2	5,1
1.Max Static	F daN	2,1	1,8	1,2	0,8
	d mm	2,9	3,6	5,3	7,4
2.Max Shock	F daN	16,6	10,8	7,6	4,7
	d mm	14	13	20	26
3.Max Vibration	2a mm	1,6	1,5	2,2	2,9
	f Hz	11,3	11,2	9,2	8



SHEAR OR ROLL

MP4 Series	Model	-90	-120	-145	-195
1.Max Static	F daN	1,4	1,2	0,8	0,5
	d mm	5,7	7,4	10,5	16,4
2.Max Shock	F daN	5,5	4,7	2,9	1,8
	d mm	16	20	28	39
3.Max Vibration	2a mm	1,8	2,2	3,1	4,4
	f Hz	9,2	8,2	6,9	5,8

1. Max static load (F) with corresponding deflection (d)
 2. Max shock load (F) with corresponding deflection (d)
 3. Uncoupled resonant frequency (f) under max static loading 1. and max peak to peak sinusoidal vibration input (2a)
- *IMPORTANT:** Performance characteristics are given here for reference only. They can be increased under specific conditions. Contact us

TYPICAL SHOCK/VIBRATION SPECIFICATIONS:

Air	AIR 7306, MIL-E-5400, MIL-C-172, MIL-STD-810
Ground Forces	GAM EG13A, SEFT 001, MIL-STD-810, VG 9533
Marine	GAM EG13C, IT25-21/96-31/15-86, MIL-S-167, MIL-S-901, STANAG 042, BV 043.73, BV 044
Others	GAM EMB1, GAM EMBT4, DEF STAN 07-55, IEC 571, FINABEL 2C