


# WIRE ROPE ISOLATOR

DEFINITION  
**series HH68**



- All metal multidirectional anti-vibration/shock mounts
  - Exceptional reliability and long life
  - High damping
  - No aging
  - Corrosion resistant
  - Unequalled temperature range : - 180°C to 300°C (-290°F to 570°F)
  - Great adaptability/versatility
- Specials on request**  
(material size and number of loops, etc.)

Dimensions are in millimeters. For reference only

| SERIES                                                        |
|---------------------------------------------------------------|
| Materials and finishes<br>(meets RoHS requirements)           |
| <b>HH68</b>                                                   |
| <b>Cable:</b><br>stainless steel<br>galvanized available: HHG |
| <b>Retainer bars:</b><br>aluminium alloy/<br>SurTec           |
| <b>Screws:</b><br>alloy steel/zinc plate                      |
| <b>Inserts:</b><br>stainless steel                            |
| All stainless steel: HHSS                                     |
| Other materials on request                                    |

| MODEL | height<br>H (mm) | width<br>W (mm) | weight<br>(kg) |
|-------|------------------|-----------------|----------------|
| -24   | 133              | 140             | 4.1            |
| -28   | 152              | 165             | 4.7            |
| -32   | 159              | 178             | 4.9            |
| -34   | 175              | 195             | 5.4            |
| -36   | 190              | 210             | 5.7            |
| -44   | 216              | 235             | 6.4            |

| INTERFACES                                    |                            |                                                  |               |
|-----------------------------------------------|----------------------------|--------------------------------------------------|---------------|
| fixtures holes D                              | Bar 1                      |                                                  |               |
|                                               | 2 through holes<br>̢13,5mm | 2 through holes<br>̢13,5mm<br>countersunk<br>90° | 2 inserts M12 |
| Bar 2                                         |                            |                                                  |               |
| 2 through holes<br>̢13,5mm                    | TM2                        | not standard                                     | not standard  |
| 2 through holes<br>̢13,5mm<br>countersunk 90° | TCM                        | CM2                                              | not standard  |
| 2 inserts M12                                 | TIM                        | CIM                                              | IM2           |

|   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|
| H | H | 6 | 8 | - | 2 | 4 | 0 | 4 | C | I | M |
|---|---|---|---|---|---|---|---|---|---|---|---|


**SERIE:** HH68  
'Half-Helical' mount from  
the HH68 series

**MODEL:** -24  
height: 133mm  
width: 140mm  
weight: 4.1kg

**LOOPS:** 04  
Serie  
standard is  
04 loops


**INTERFACE:** CIM  
2 through holes ̢13,5mm  
countersunk 90° in bar 1,  
2 inserts M12 in bar 2






## COMPRESSION AND TENSION

| HH68 Series     | Model | -24  | -28  | -32  | -34  | -36  | -44  |
|-----------------|-------|------|------|------|------|------|------|
| 1.Max Static    | F daN | 809  | 579  | 500  | 416  | 358  | 285  |
|                 | d mm  | 8.5  | 12   | 13.8 | 16.4 | 18.6 | 22.3 |
| 2.Max Shock     | F daN | 2427 | 1738 | 1502 | 1248 | 1074 | 855  |
|                 | d mm  | 51   | 68   | 74   | 89   | 102  | 126  |
| 3.Max Vibration | 2a mm | 5.6  | 7.5  | 8.2  | 9.8  | 11.3 | 13.9 |
|                 | f Hz  | 6.6  | 5.7  | 5.4  | 4.9  | 4.6  | 4.2  |
| 1.Max Static    | F daN | 809  | 579  | 500  | 416  | 358  | 285  |
|                 | d mm  | 5.6  | 8.2  | 9.6  | 11.3 | 12.8 | 15.2 |
| 2.Max Shock     | F daN | 6838 | 5165 | 4697 | 3864 | 3279 | 2553 |
|                 | d mm  | 21   | 32   | 39   | 45   | 51   | 59   |
| 3.Max Vibration | 2a mm | 2.3  | 3.5  | 4.3  | 5    | 5.6  | 6.6  |
|                 | f Hz  | 10.2 | 8.3  | 7.6  | 7    | 6.6  | 6.1  |



## COMPRESSION/ROLL 45° - TENSION/ROLL 45°

| HH68 Series     | Model | -24  | -28  | -32  | -34  | -36  | -44  |
|-----------------|-------|------|------|------|------|------|------|
| 1.Max Static    | F daN | 606  | 434  | 375  | 312  | 268  | 213  |
|                 | d mm  | 11.1 | 13.9 | 18.1 | 21.7 | 25.3 | 25.4 |
| 2.Max Shock     | F daN | 1531 | 1109 | 969  | 804  | 689  | 546  |
|                 | d mm  | 76   | 102  | 112  | 133  | 153  | 189  |
| 3.Max Vibration | 2a mm | 8.5  | 11.3 | 12.3 | 14.7 | 16.9 | 20.8 |
|                 | f Hz  | 5    | 4.3  | 4    | 3.7  | 3.4  | 3.2  |
| 1.Max Static    | F daN | 606  | 434  | 375  | 312  | 268  | 213  |
|                 | d mm  | 7    | 9.9  | 11.2 | 14.7 | 16.3 | 18.6 |
| 2.Max Shock     | F daN | 3359 | 2547 | 2325 | 1911 | 1620 | 1260 |
|                 | d mm  | 24   | 36   | 44   | 52   | 58   | 68   |
| 3.Max Vibration | 2a mm | 2.7  | 4    | 5    | 5.8  | 6.4  | 7.5  |
|                 | f Hz  | 8.2  | 6.7  | 6.1  | 5.7  | 5.4  | 4.9  |



## SHEAR OR ROLL

| HH68 Series     | Model | -24  | -28  | -32  | -34  | -36  | -44  |
|-----------------|-------|------|------|------|------|------|------|
| 1.Max Static    | F daN | 404  | 289  | 250  | 208  | 179  | 142  |
|                 | d mm  | 11.6 | 16.8 | 17.9 | 23.1 | 25.5 | 32.8 |
| 2.Max Shock     | F daN | 1847 | 1360 | 1233 | 992  | 828  | 629  |
|                 | d mm  | 40   | 57   | 65   | 77   | 87   | 105  |
| 3.Max Vibration | 2a mm | 4.5  | 6.3  | 7.2  | 8.5  | 9.7  | 11.6 |
|                 | f Hz  | 2.8  | 2.4  | 2.2  | 2    | 1.9  | 1.8  |

1. Max static load (F) with corresponding deflection (d)
2. Max shock load (F) with corresponding deflection (d)
3. Uncoupled resonant frequency (f) under max static loading 1. and max peak to peak sinusoidal vibration input (2a)

**\*IMPORTANT:** Performance characteristics are given here for reference only. They can be increased under specific conditions. Contact us

## TYPICAL SHOCK/VIBRATION SPECIFICATIONS:

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Air           | AIR 7306, MIL-E-5400, MIL-C-172, MIL-STD-810                                        |
| Ground Forces | GAM EG13A, SEFT 001, MIL-STD-810, VG 9533                                           |
| Marine        | GAM EG13C, IT25-21/96-31/15-86, MIL-S-167, MIL-S-901, STANAG 042, BV 043.73, BV 044 |
| Others        | GAM EMB1, GAM EMBT4, DEF STAN 07-55, IEC 571, FINABEL 2C                            |

